

Laidlaw Corporation
5326 Industrial Park Road
Metropolis, IL 62960

Date Signed: 3-1-04

Transportation: Chemtrec

Prepared By: A. Boykin & John T. Beckman

Emergency: 1-800-424-9300

MATERIAL SAFETY DATA SHEET

I. IDENTIFICATION

PRODUCT NAME: Collar Solution
CHEMICAL NAME: Spot and Stain Remover
CAS NUMBER: MIXTURE
EMERGENCY TELEPHONE NUMBER: (618) 524-9394

II. COMPONENTS AND HAZARD INFORMATION

HAZARDOUS COMPONENT	CAS NO. OF COMPONENT	TLV OF COMPONENT	OSHA PEL	APPROXIMATE CONCENTRATION
Butyl Cellosolve	111-76-2	25 ppm	25 ppm	10.0%
Aromatic 100	64742-95-6	50 ppm	50 ppm	10.0%

D.O.T. Hazard Classification: Liquid, Non-Hazardous
Hazardous Materials Identification System (HMIS)

Health	Flammability	Reactivity	BASIS
<u>1</u>	<u>0</u>	<u>0</u>	<u>Recommended by Laidlaw</u>
<u>TLV for Total Product</u>			<u>BASIS</u>
<u>103 ppm</u>			<u>Calculated TLV REF ACGIH</u>

III. PHYSICAL DATA

Boiling Point >200°F Vapor Density Not determined.
Vapor Pressure Not determined. Percent Volatiles 96.0%
Specific Gravity 1.0030 Evaporation Rate Not determined.

IV. FIRE AND EXPLOSION DATA

Flash Point (°F TCC) Initial 143°F
Extinguishing Media None.

Special Firefighting Procedures As appropriate for surrounding fire.

Unusual Fire & Explosion Hazards None known.

National Fire Protection Association (NFPA) - Hazard Identification

Health	Flammability	Reactivity	BASIS
<u>1</u>	<u>0</u>	<u>0</u>	<u>Recommended by Laidlaw</u>

V. HEALTH HAZARD DATA

Effects of Overexposure:

Eyes: Can cause severe irritation.

Skin: Prolonged or repeated contact may cause moderate irritation.

Breathing: Excessive inhalation of vapors may cause nasal and respiratory irritation.

Swallowing: Can cause gastrointestinal irritation. Aspiration of material into lungs can cause chemical pneumonitis, which can be fatal.

COLLAR SOLUTION

First Aid Procedures:

Swallowing: Do not induce vomiting; get medical attention.

Skin: Wash with soap and water.

Inhalation: Remove individual to fresh air.

Eyes: Flush with copious amounts of water.

Health studies have shown that health risks vary from person to person. As a precaution exposure to liquids, vapors, misty fumes or dust should be minimized.

VI. REACTIVITY DATA

Hazardous Polymerization: Cannot occur.

Stability: Stable.

Incompatibility: Avoid strong oxidizing agents.

Hazardous Decomposition Products: May form toxic materials at high temperatures.

VII. SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled:

Absorb on absorbent material and dispose of in accordance with local, state, and federal regulations. Keep out of water supply and check local regulations before flushing into sewage system.

VIII. PROTECTION AND PRECAUTIONS

Respiratory Protection: Use approved vapor respirator if needed.

Ventilation: Provide sufficient ventilation to maintain exposure below TLV.

Protective Gloves: Not necessary.

Eye Protection: Splash goggles or face shield when eye contact may occur.

Other Protective Equipment: None.

IX. PRECAUTIONS OR OTHER COMMENTS

Precautions to be taken in handling and storing: Maintain good housekeeping. Avoid contact with eyes. Wash thoroughly after handling. Use with adequate ventilation.

The information and recommendations accumulated herein are to the best of Laidlaw's knowledge and belief, accurate and reliable as of the date issued. Laidlaw does not warrant or guarantee their accuracy or reliability, and shall not be liable for any loss or damage arising out of the use thereof.

HMIS and NFPA recommended ratings are based upon the criteria supplied by the developers of these rating systems together with Laidlaw's interpretation of the available data.