

Laidlaw Corporation
5326 Industrial Park Road
Metropolis, IL 62960

Date Signed: 3-1-04

Transportation: Chemtrec

Prepared By: A. Boykin & John T. Beckman

Emergency: 1-800-424-9300

MATERIAL SAFETY DATA SHEET

I. IDENTIFICATION

PRODUCT NAME: Drycon
CHEMICAL NAME: Sizing Agent
CAS NUMBER: MIXTURE
EMERGENCY TELEPHONE NUMBER: (618) 524-9394

II. COMPONENTS AND HAZARD INFORMATION

HAZARDOUS COMPONENT	CAS NO. OF COMPONENT	TLV OF COMPONENT	OSHA PEL	APPROXIMATE CONCENTRATION
Mineral Spirits	64742-88-7	100 ppm	100 ppm	30.0%
Aromatic 150	64742-95-6	100 ppm	100 ppm	5.0%

D.O.T. Hazard Classification: Combustible Liquid NOS, (Contains Petroleum Distillates), NA 1993, PG III
Hazardous Materials Identification System (HMIS)

Health 1	Flammability 1	Reactivity 1	BASIS Recommended by Laidlaw BASIS Calculated TLV REF ACGIH
TLV for Total Product 100 ppm			

III. PHYSICAL DATA

Boiling Point 374°F Vapor Density Not determined.
Vapor Pressure Not determined. Percent Volatiles 35.0%
Specific Gravity 0.9000 Evaporation Rate Not determined.

IV. FIRE AND EXPLOSION DATA

Flash Point (°F TCC) 201°F
Extinguishing Media Carbon dioxide, foam, dry chemical.

Special Firefighting Procedures Do not use water. Self-contained breathing equipment operated in pressure mode.

Unusual Fire & Explosion Hazards None.

National Fire Protection Association (NFPA) - Hazard Identification

Health 1	Flammability 1	Reactivity 1	BASIS Recommended by Laidlaw
-------------	-------------------	-----------------	---------------------------------

V. HEALTH HAZARD DATA

Effects of Overexposure:

Eyes: Mild transient irritant.

Skin: May cause moderate irritation with prolonged contact.

Breathing: Dizziness may occur in confined non-ventilated area.

Swallowing: Can cause nausea, vomiting, diarrhea.

DRYCON

First Aid Procedures:

- Swallowing: Do not induce vomiting. Get medical attention.
- Skin: Thoroughly wash exposed area with soap and water.
- Inhalation: Remove individual to fresh air.
- Eyes: Flush with water, lifting eyelids occasionally.

Health studies have shown that health risks vary from person to person. As a precaution exposure to liquids, vapors, misty fumes or dust should be minimized.

VI. REACTIVITY DATA

- Hazardous Polymerization: Cannot occur.
- Stability: Stable.
- Incompatibility: Avoid strong oxidizing agents.
- Hazardous Decomposition Products: May form toxic hydrocarbons at high temperatures.

VII. SPILL OR LEAK PROCEDURES

- Steps to be taken in case material is released or spilled:
- Soak up with absorbent material and dispose of in accordance with local, state and federal regulations.
-
-
-
-
-

VIII. PROTECTION AND PRECAUTIONS

- Respiratory Protection: Use approved organic vapor respirator if exposure may or does exceed TLV limit.
 - Ventilation: Provide sufficient ventilation to maintain exposure below TLV.
 - Protective Gloves: Not required.
 - Eye Protection: Wear safety glasses or goggles as appropriate.
 - Other Protective Equipment: None required.
-
-
-
-
-

IX. PRECAUTIONS OR OTHER COMMENTS

Precautions to be taken in handling and storing: Maintain good housekeeping. Avoid contact with eyes. Wash thoroughly after handling. Use with adequate ventilation.

The information and recommendations accumulated herein are to the best of Laidlaw's knowledge and belief, accurate and reliable as of the date issued. Laidlaw does not warrant or guarantee their accuracy or reliability, and shall not be liable for any loss or damage arising out of the use thereof.

HMIS and NFPA recommended ratings are based upon the criteria supplied by the developers of these rating systems together with Laidlaw's interpretation of the available data.