

Laidlaw Corporation
5326 Industrial Park Road
Metropolis, IL 62960

Date Signed: 3-1-04

Transportation: Chemtrec

Prepared By: John T. Beckman

Emergency: 1-800-424-9300

MATERIAL SAFETY DATA SHEET

I. IDENTIFICATION

PRODUCT NAME: Hydrocarbon (HC) Wetspo
CHEMICAL NAME: Spot and stain remover
CAS NUMBER: MIXTURE
EMERGENCY TELEPHONE NUMBER: (618) 524-9394

II. COMPONENTS AND HAZARD INFORMATION

HAZARDOUS COMPONENT	CAS NO. OF COMPONENT	TLV OF COMPONENT	OSHA PEL	APPROXIMATE CONCENTRATION
Butyl Cellosolve	111-76-2	25 ppm	25 ppm	25.00%
Potassium Hydroxide	1310-58-3	2 mg/m ³	2 mg/m ³	2.00%
Aromatic 100	64742-95-6	50 ppm	50 ppm	25.00%

This product contains Potassium Hydroxide which is subject to the reporting requirements of SARA III.

D.O.T. Hazard Classification: Combustible Liquid NOS, (Contains Petroleum Distillates), NA 1993, PG III

Hazardous Materials Identification System (HMIS)

Health 1	Flammability 2	Reactivity 0	BASIS Recommended by Laidlaw BASIS Calculated TLV REF ACGIH
TLV for Total Product 50 ppm			

III. PHYSICAL DATA

Boiling Point 206°F Vapor Density Not determined.
Vapor Pressure Not determined. Percent Volatiles 96%
Specific Gravity 0.912 Evaporation Rate Not determined.

IV. FIRE AND EXPLOSION DATA

Flash Point (°F TCC) 122°F
Extinguishing Media Class B & C dry chemical extinguisher.

Special Firefighting Procedures Self-contained breathing apparatus with full facepiece operated in pressure mode.

Unusual Fire & Explosion Hazards Vapors can be ignited by high energy source or other ignition sources at location distant from the handling point.

National Fire Protection Association (NFPA) - Hazard Identification

Health 1	Flammability 2	Reactivity 0	BASIS Recommended by Laidlaw
-------------	-------------------	-----------------	---------------------------------

V. HEALTH HAZARD DATA

Effects of Overexposure:

Eyes: Can cause severe irritation.
Skin: Prolonged or repeated contact may cause moderate irritation.
Breathing: Excessive inhalation of vapors may cause nasal and respiratory irritation.
Swallowing: Can cause nausea, diarrhea, and gastrointestinal irritation. Aspiration of material into lungs can cause pneumonitis, which can be fatal.

HYDROCARBON (HC) WETSPO

First Aid Procedures:

- Swallowing: Do not induce vomiting. Seek medical attention.
- Skin: Wash exposed area with soap and water.
- Inhalation: Remove to fresh air; if breathing is difficult administer oxygen.
- Eyes: Flush with water for at least 15 minutes. If irritation persists, consult physician.

Health studies have shown that health risks vary from person to person. As a precaution exposure to liquids, vapors, misty fumes or dust should be minimized.

VI. REACTIVITY DATA

- Hazardous Polymerization: Cannot occur.
- Stability: Stable.
- Incompatibility: Avoid strong oxidizing agents.
- Hazardous Decomposition Products: May form toxic hydrocarbons at high temperatures.

VII. SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled:

Absorb on paper or other absorbent material and dispose of in accordance with local, state and federal regulations. Keep out of water supply and sewage system. Dispose of in a permitted hazardous waste management facility.

VIII. PROTECTION AND PRECAUTIONS

- Respiratory Protection: Use approved organic vapor respirator if exposure may or does exceed the TLV limit.
 - Ventilation: Provide sufficient ventilation to maintain exposure below TLV.
 - Protective Gloves: Not necessary, but can be used.
 - Eye Protection: Splash goggles or face shield if eye contact is likely to occur.
 - Other Protective Equipment: None.
-
-
-
-

IX. PRECAUTIONS OR OTHER COMMENTS

Precautions to be taken in handling and storing: Maintain good housekeeping. Avoid contact with eyes. Wash thoroughly after handling. Use with adequate ventilation.

The information and recommendations accumulated herein are to the best of Laidlaw's knowledge and belief, accurate and reliable as of the date issued. Laidlaw does not warrant or guarantee their accuracy or reliability, and shall not be liable for any loss or damage arising out of the use thereof.

HMIS and NFPA recommended ratings are based upon the criteria supplied by the developers of these rating systems together with Laidlaw's interpretation of the available data.