

Laidlaw Corporation  
5326 Industrial Park Road  
Metropolis, IL 62960

Date Signed: 3-1-04

Transportation: Chemtrec

Prepared By: John T. Beckman

Emergency: 1-800-424-9300

**MATERIAL SAFETY DATA SHEET**

**I. IDENTIFICATION**

PRODUCT NAME: Kolor-Brite  
CHEMICAL NAME: Anionic Detergent  
CAS NUMBER: MIXTURE  
EMERGENCY TELEPHONE NUMBER: (618) 524-9394

**II. COMPONENTS AND HAZARD INFORMATION**

HAZARDOUS COMPONENT	CAS NO. OF COMPONENT	TLV OF COMPONENT	OSHA PEL	APPROXIMATE CONCENTRATION
Paraffin Oil	64741-89-5	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	20.0%
Hexylene Glycol	107-41-5	25 ppm	25 ppm	5.0%

D.O.T. Hazard Classification: Liquid, Non-Hazardous  
Hazardous Materials Identification System (HMIS)

Health	Flammability	Reactivity	BASIS
<u>1</u>	<u>1</u>	<u>1</u>	<u>Recommended by Laidlaw</u>
<u>TLV for Total Product</u>			<u>BASIS</u>
<u>50 ppm</u>			<u>Calculated TLV REF ACGIH</u>

**III. PHYSICAL DATA**

Boiling Point 216°F Vapor Density Not determined.  
Vapor Pressure Not determined. Percent Volatiles 98.0%  
Specific Gravity 0.980 Evaporation Rate Not determined.

**IV. FIRE AND EXPLOSION DATA**

Flash Point (°F TCC) >200°F  
Extinguishing Media Alcohol foam, water fog or dry chemical.

Special Firefighting Procedures Self-contained breathing equipment with full facepiece operated in positive mode.

Unusual Fire & Explosion Hazards Vapors can be ignited by high energy sources or other ignition sources at location distant from handling point.

National Fire Protection Association (NFPA) - Hazard Identification

Health	Flammability	Reactivity	BASIS
<u>1</u>	<u>1</u>	<u>1</u>	<u>Recommended by Laidlaw</u>

**V. HEALTH HAZARD DATA**

Effects of Overexposure:

Eyes: Can cause severe irritation.

Skin: Prolonged or repeated contact may cause moderate irritation.

Breathing: Excessive inhalation of vapors may cause nasal and respiratory irritation.

Swallowing: Can cause gastrointestinal irritation. Aspiration of material into lungs can cause chemical pneumonitis, which can be fatal.

**KOLOR-BRITE**

First Aid Procedures:

- Swallowing: Do not induce vomiting; get medical attention.
- Skin: Wash with soap and water.
- Inhalation: Remove individual to fresh air.
- Eyes: Flush with copious amounts of water.

Health studies have shown that health risks vary from person to person. As a precaution exposure to liquids, vapors, misty fumes or dust should be minimized. Keep away from children.

---

**VI. REACTIVITY DATA**

- Hazardous Polymerization: Cannot occur.
- Stability: Stable.
- Incompatibility: Avoid strong oxidizing agents.
- Hazardous Decomposition Products: May form toxic materials at high temperatures.

---

**VII. SPILL OR LEAK PROCEDURES**

Steps to be taken in case material is released or spilled:

- Absorb on paper or other absorbent material. Dispose of in accordance with local, state and federal regulations.
- 
- 
- 
- 
- 

---

**VIII. PROTECTION AND PRECAUTIONS**

- Respiratory Protection: Use approved vapor respirator if needed.
  - Ventilation: Provide sufficient ventilation to maintain exposure below TLV.
  - Protective Gloves: Not necessary.
  - Eye Protection: Use splash goggles or faceshield when eye contact may occur.
  - Other Protective Equipment: None.
- 
- 
- 
- 
- 

---

**IX. PRECAUTIONS OR OTHER COMMENTS**

Precautions to be taken in handling and storing: Maintain good housekeeping. Avoid contact with eyes. Wash thoroughly after handling. Use with adequate ventilation.

The information and recommendations accumulated herein are to the best of Laidlaw's knowledge and belief, accurate and reliable as of the date issued. Laidlaw does not warrant or guarantee their accuracy or reliability, and shall not be liable for any loss or damage arising out of the use thereof.

HMIS and NFPA recommended ratings are based upon the criteria supplied by the developers of these rating systems together with Laidlaw's interpretation of the available data.